



SMW7B Buttonless Monitor System

Call for Big Savings 574-807-6004

This buttonless monitor was designed to only turn on when the vehicle is in reverse. It is now a standard system installed at OEMs and major fleet companies. The monitor supports up to (1) Verity camera. The SMW7B includes our ADD22H heavy duty mount and (1) 65' camera cable. Ideal for limited installation space!

MONITOR SPECIFICATIONS (Part #MK07B)

MONITOR SPECIFICATIONS

- Screen size: 7-inch digital screen (16:9)
- Long Life High Resolution: 800 x 480 Pixel (RGB)
- System: PAL/NTSC Auto Select
- Contrast: 500:1
- Brightness: 450cd/m2
- Power supply: DC 12V~24V with reverse polarity protection
- Operation Temperature: -30~70C
- Storage Temperature: -40~80C
- 1 AV color-coded input with color-coded trigger wire
- Auto blue screen when no signal



Features: removable sun shield, auto light sensor dimming for buttons and LCD screen, LED blue light buttons, high-quality processor, in-line waterproof fuse, easy-to-use OSD menu function via buttons & remote: image delay on time 0~15s (for side cameras) Mirror/Normal image, multi-language, NEW! Adjustable guidelines.



CAMERA SPECIFICATIONS (Part #C300P)

CAMERA SPECIFICATIONS

- COLOR CCD Camera
- Shockproof: 10G
- No Audio
- Waterproof: IP69K
- Viewing angle: 193°
- Format is NTSC to ensure proper images with USA formatted DVRs
- Resolution: 700TV Lines / Effective pixel: 510 x 492
- Illumination: 1.5 Lux
- Power supply: DC 12V (powered by monitor)
- Operating Temperature: -40°~70°
- 4-pin male waterproof connector



Optional: ADD300Z
Camera Cover

574-807-6002 www.veritysafe.com Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

A division of Component Solution Services, LLC.

Woman-Owned

Est. 2002

Subject to change without notice