



SM07S4

Wide View System System includes (1) C001S Camera

Engineered to meet the commercial demands needing a wide view, without the fisheye. The system utilizes our most advanced power management system for stability in unstable electrical environments. This 7" LCD Monitor has a clear, crisp view in our durable housing. The monitor supports up to (3) Verity cameras. The SM07S includes our ADD21U "S" mount and (1) 65' camera cable. Ideal for limited installation space!

MONITOR SPECIFICATIONS (Part #MK07S)

MONITOR SPECIFICATIONS

(Monitor part #MK07S)

Screen size: 7-inch digital screen (16:9)

High Resolution: 1024 x 600 Pixel (RGB)

System: PAL/NTSC selectable

Contrast: 400:1

Brightness: 300 cd/m2

Power supply: DC 12V~24V with reverse polarity protection

Operation temperature: -30°~80°C

Storage temperature: -20°~70°C

Monitor view angle: Horz. L (70) R (70) Vert. UP (50) DOWN (70)

3 AV with shrink tube labeled trigger wires,

Auto blue screen if no signal on the activated channel.

Size: 141 x 103 x 25 mm.

Weight: 418 g.

Features: Removable HD sunshade, LCD screen, LED blue light buttons, high-quality processor, in-line waterproof fuse, easy to use OSD menu function via buttons: reversing image delay time 0~10s, Mirror/Normal image, plus horizontal flip, multi-language.



CAMERA SPECIFICATIONS (Part #C305)

CAMERA SPECIFICATIONS

Low Profile

Camera Part #C305

Horizontal Resolution: 800 TV Lines

TV System: NTSC

Image Type: CMOS PC1058

Aluminum Housing

Waterproof: IP69K (highest waterproof rating available)

Power Supply: DC 12V (powered from the monitor)

Operating Temperature: -20°C ~ +75°C

Viewing Angle: 180-degrees horizontal.



574-807-6002 www.veritysafe.com Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

A division of Component Solution Services, LLC.

Woman-Owned

Est. 2002

Subject to change without notice