



SM05J & SM07J Rear Vision Systems

Our exclusive 5-inch and 7-inch digital screens with ultra-clear image in our custom housings. 32 Major improvements were made to this system. 20 years of installs, factory line audits, tech support calls, warranty calls, and a lifetime of "it would work better and longer if we could..." went into the development of this system. 99.97 % of our systems are working flawlessly...we want 100%!



With ADD22H Slim Base mount

MONITOR SPECIFICATIONS MK05J & MK07J

Screen size: 5-inch digital screen (16:9)
Long Life High Resolution:
(5-inch 640 x 480 Pixel) (7-inch 800 x 480 Pixel) (RGB)
System: PAL/NTSC selectable
Contrast: 500:1
Brightness: 450 cd/m2
Power supply: DC 12V~24V with reverse polarity protection
Operation temperatures: -30°~70°C
Storage temperature: -40°~80°C
61" monitor harness with 2 AV color-coded aviation/waterproof connections, waterproof fuse and color-coded trigger wires.
Auto blue screen if no signal on activated channel.
Features: HD sunshade, auto light sensor dimming for buttons and LCD screen, LED blue light buttons, high quality processor, in-line waterproof fuse, easy to use OSD menu function via buttons & remote: reversing image delay time 0~10s, (for side cameras) Mirror/Normal image, plus horizontal flip per signal channel, multi-language, featuring adjustable guidelines.



CAMERA SPECIFICATIONS C001J

Horizontal Resolution:700 TV Lines
TV System: NTSC
Image Type: 1/3 Inch Color CCD Sharp® or equivalent
(no cheap off brands used)
Effective pixel: 510 x 492
Illumination: 0 Lux (built-in 20 high output IR LEDs for night vision)
Aluminum housing.
Waterproof: IP69K
Power supply: DC 12V (from monitor)
Shockproof: 10G
Operating temperature: -40°~70°C
Built-in microphone
Viewing angle: 120°



Optional ADD100Z
Aluminum Camera Cover
Available for J-series Camera

574-807-6002 www.verityrvs.com Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

Woman-Owned

A division of Component Solution Services, LLC.

Est. 2002

Subject to change without notice